



Large atlantic 27.55" sheppards crook post top streetlighting


IP65 ◆ ▲ ▲ /EN 60598/CLASS I ⊕ / ▽ / CE / IK07



Suitable for wet locations

An outdoor post top street and amenity lantern with a high performance optical system ensures improved visibility and reduced glare. It uses energy saving compact fluorescent lamps as well as metal halide and high pressure sodium lamps. These post top luminaires are designed for pole heights 118.1" to 236.2" and are assembled for installation in single or double configurations. Developed for car parks, footpaths, pedestrian areas, precincts, parks, gardens and building perimeters.

Low copper content die-cast aluminium housing with high corrosion resistance and extruded aluminum arm bracket. Stainless steel screws. Durable silicone rubber gasket and clear high impact resistant UV stabilized polycarbonate lens. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear and anodized high purity 95% reflective aluminum reflector.




Product Family







UAA-20651-1-1



Large atlantic dia. 27.5" sheppards crook single lantern post top.

Model No.	Lamp	Holder	Lumen	Weight	Picture
UAA-20651-1-1	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	50.4 lb.	1
UAA-20652-1-1	PMH-ED17 70w.	MED	4000	50.4 lb.	1
UAA-20653-1-1	PMH-ED17 100w.	MED	6500	50.4 lb.	1
UAA-20654-1-1	PMH-ED17 150w.	MED	10000	54.4 lb.	1
UAA-20655-1-1	HPS-ED17 70w.	MED	5450	52.6 lb.	1
UAA-20656-1-1	HPS-ED17 100w.	MED	8550	52.6 lb.	1
UAA-20657-1-1	HPS-ED17 150w.	MED	14400	54.4 lb.	1
UAA-20651-1-2	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	50.4 lb.	2
UAA-20652-1-2	PMH-ED17 70w.	MED	4000	50.4 lb.	2
UAA-20653-1-2	PMH-ED17 100w.	MED	6500	50.4 lb.	2
UAA-20654-1-2	PMH-ED17 150w.	MED	10000	54.4 lb.	2
UAA-20655-1-2	HPS-ED17 70w.	MED	5450	52.6 lb.	2
UAA-20656-1-2	HPS-ED17 100w.	MED	8550	52.6 lb.	2
UAA-20657-1-2	HPS-ED17 150w.	MED	14400	54.4 lb.	2
UAA-20651-2-1	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	50.4 lb.	3
UAA-20652-2-1	PMH-ED17 70w.	MED	4000	50.4 lb.	3
UAA-20653-2-1	PMH-ED17 100w.	MED	6500	50.4 lb.	3
UAA-20654-2-1	PMH-ED17 150w.	MED	10000	54.4 lb.	3
UAA-20655-2-1	HPS-ED17 70w.	MED	5450	52.6 lb.	3
UAA-20656-2-1	HPS-ED17 100w.	MED	8550	52.6 lb.	3
UAA-20657-2-1	HPS-ED17 150w.	MED	14400	54.4 lb.	3
UAA-20651-2-2	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	50.4 lb.	4
UAA-20652-2-2	PMH-ED17 70w.	MED	4000	50.4 lb.	4
UAA-20653-2-2	PMH-ED17 100w.	MED	6500	50.4 lb.	4
UAA-20654-2-2	PMH-ED17 150w.	MED	10000	54.4 lb.	4
UAA-20655-2-2	HPS-ED17 70w.	MED	5450	52.6 lb.	4
UAA-20656-2-2	HPS-ED17 100w.	MED	8550	52.6 lb.	4
UAA-20657-2-2	HPS-ED17 150w.	MED	14400	54.4 lb.	4




Single: EPA=2.45 ft²

Picture 1



(1) Swept shade




Single: EPA=2.38 ft²

Picture 2



(2) Straight shade




Single: EPA=2.58 ft²

Picture 3



(1) Dome top






Single: EPA=2.51 ft²



Picture 4




(2) Cone top



Tenon post top



Steel post
Mounting detail



Aluminium post
Mounting detail








UAA-20661-2-2


Large atlantic dia. 27.5" sheppards crook double lantern post top.

Model No.	Lamp	Holder	Lumen	Weight	Picture
UAA-20661-1-1	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	72.0 lb.	1
UAA-20662-1-1	PMH-ED17 2x70w.	MED	2X4000	74.3 lb.	1
UAA-20663-1-1	PMH-ED17 2x100w.	MED	2X6500	74.7 lb.	1
UAA-20664-1-1	PMH-ED17 2x150w.	MED	2X10000	74.7 lb.	1
UAA-20665-1-1	HPS-ED17 2x70w.	MED	2X5450	74.3 lb.	1
UAA-20666-1-1	HPS-ED17 2x100w.	MED	2X8550	74.7 lb.	1
UAA-20667-1-1	HPS-ED17 2x150w.	MED	2X14400	74.7 lb.	1
UAA-20661-1-2	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	72.0 lb.	2
UAA-20662-1-2	PMH-ED17 2x70w.	MED	2X4000	74.3 lb.	2
UAA-20663-1-2	PMH-ED17 2x100w.	MED	2X6500	74.7 lb.	2
UAA-20664-1-2	PMH-ED17 2x150w.	MED	2X10000	74.7 lb.	2
UAA-20665-1-2	HPS-ED17 2x70w.	MED	2X5450	74.3 lb.	2
UAA-20666-1-2	HPS-ED17 2x100w.	MED	2X8550	74.7 lb.	2
UAA-20667-1-2	HPS-ED17 2x150w.	MED	2X14400	74.7 lb.	2
UAA-20661-2-1	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	72.0 lb.	3
UAA-20662-2-1	PMH-ED17 2x70w.	MED	2X4000	74.3 lb.	3
UAA-20663-2-1	PMH-ED17 2x100w.	MED	2X6500	74.7 lb.	3
UAA-20664-2-1	PMH-ED17 2x150w.	MED	2X10000	74.7 lb.	3
UAA-20665-2-1	HPS-ED17 2x70w.	MED	2X5450	74.3 lb.	3
UAA-20666-2-1	HPS-ED17 2x100w.	MED	2X8550	74.7 lb.	3
UAA-20667-2-1	HPS-ED17 2x150w.	MED	2X14400	74.7 lb.	3
UAA-20661-2-2	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	72.0 lb.	4
UAA-20662-2-2	PMH-ED17 2x70w.	MED	2X4000	74.3 lb.	4
UAA-20663-2-2	PMH-ED17 2x100w.	MED	2X6500	74.7 lb.	4
UAA-20664-2-2	PMH-ED17 2x150w.	MED	2X10000	74.7 lb.	4
UAA-20665-2-2	HPS-ED17 2x70w.	MED	2X5450	74.3 lb.	4
UAA-20666-2-2	HPS-ED17 2x100w.	MED	2X8550	74.7 lb.	4
UAA-20667-2-2	HPS-ED17 2x150w.	MED	2X14400	74.7 lb.	4




Double: EPA=5.17 ft²

Picture 1




Double: EPA=5.10 ft²

Picture 2





Double: EPA=5.30 ft²

Picture 3





Double: EPA=5.23 ft²



Picture 4



Tenon post top



Steel post
Mounting detail



Aluminium post
Mounting detail



(1) Swept shade



(2) Straight shade



(1) Dome top



(2) Cone top

Large atlantic dia. 27.56" sheppards crook post top streetlighting

Art. UAA-20658-1-1 HPS-ED17 150w. pole height 19.68ft road width 32.8ft and the distance between luminaires are 32.8ft





Large atlantic 700 mm. sheppards crook post top streetlighting LED

IP65 ◆ ▲ ▲ / EN 60598/CLASS I ⚡ / ▽ / CE / IK07



Suitable for wet locations

An outdoor post top street and amenity lantern with a high performance optical system ensures improved visibility and reduced glare using. These post top luminaires are designed for pole heights 118.1" to 236.2" and are assembled for installation in single or double configurations. Developed for car parks, footpaths, pedestrian areas, precincts, parks, gardens and building perimeters.

Low copper content die-cast aluminium housing with high corrosion resistance and extruded aluminum arm bracket. Stainless steel screws. Durable silicone rubber gasket and clear impact resistant UV stabilized polycarbonate lens. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral driver.



Product Family



P.324 Atlantic P.333 Atlantic small shade P.334 Atlantic medium shade P.339 Large Atlantic sheppards crook



P.341 Large Atlantic sheppards crook LED P.343 Atlantic sheppards crook P.499 Atlantic bollard P.499 Atlantic 1 pillar light



P.500 Atlantic 2 pillar light P.581 Atlantic small shade P.582 Atlantic medium shade P.589 Atlantic sheppard crook



P.593 Large Atlantic sheppards crook P.597 Large Atlantic sheppards crook LED P.599 Large Atlantic sheppards crook for urban areas P.681 Atlantic small shade




P.681 Atlantic medium shade






UAA-20659-1-1



UAA-20669-2-2







Large atlantic dia 27.5" sheppards crook single lantern post top LED

Model No.	Lamp	Light output	LED colour	Power W	Weight	Picture	Dimmable 1-10V
UAA-20659-1-1-W27	36 LED	2684 lm	2700K	55	50.4 lb.	1	•
UAA-20659-1-1-W30	36 LED	2697 lm	3000K	55	50.4 lb.	1	•
UAA-20659-1-1-W40	36 LED	3083 lm	4000K	55	50.4 lb.	1	•
UAA-20659-1-2-W27	36 LED	2684 lm	2700K	55	50.4 lb.	2	•
UAA-20659-1-2-W30	36 LED	2967 lm	3000K	55	50.4 lb.	2	•
UAA-20659-1-2-W40	36 LED	3083 lm	4000K	55	50.4 lb.	2	•
UAA-20659-2-1-W27	36 LED	2684 lm	2700K	55	50.4 lb.	3	•
UAA-20659-2-1-W30	36 LED	2697 lm	3000K	55	50.4 lb.	3	•
UAA-20659-2-1-W40	36 LED	3083 lm	4000K	55	50.4 lb.	3	•
UAA-20659-2-2-W27	36 LED	2684 lm	2700K	55	50.4 lb.	4	•
UAA-20659-2-2-W30	36 LED	2697 lm	3000K	55	50.4 lb.	4	•
UAA-20659-2-2-W40	36 LED	3083 lm	4000K	55	50.4 lb.	4	•

Large atlantic dia 27.5" sheppards crook double lantern post top LED

Model No.	Lamp	Light output	LED colour	Power W	Weight	Picture	Dimmable 1-10V
UAA-20669-1-1-W27	2x36 LED	2X2684 lm	2700K	2x55	72.0 lb.	1	•
UAA-20669-1-1-W30	2x36 LED	2X2697 lm	3000K	2x55	72.0 lb.	1	•
UAA-20669-1-1-W40	2x36 LED	2X3083 lm	4000K	2x55	72.0 lb.	1	•
UAA-20669-1-2-W27	2x36 LED	2X2684 lm	2700K	2x55	72.0 lb.	2	•
UAA-20669-1-2-W30	2x36 LED	2X2697 lm	3000K	2x55	72.0 lb.	2	•
UAA-20669-1-2-W40	2x36 LED	2X3083 lm	4000K	2x55	72.0 lb.	2	•
UAA-20669-2-1-W27	2x36 LED	2X2684 lm	2700K	2x55	72.0 lb.	3	•
UAA-20669-2-1-W30	2x36 LED	2X2697 lm	3000K	2x55	72.0 lb.	3	•
UAA-20669-2-1-W40	2x36 LED	2X3083 lm	4000K	2x55	72.0 lb.	3	•
UAA-20669-2-2-W27	2x36 LED	2X2684 lm	2700K	2x55	72.0 lb.	4	•
UAA-20669-2-2-W30	2x36 LED	2X2697 lm	3000K	2x55	72.0 lb.	4	•
UAA-20669-2-2-W40	2x36 LED	2X3083 lm	4000K	2x55	72.0 lb.	4	•



Large atlantic 700 mm. sheppards crook streetlighting for urban areas


IP65 ◆ ▲ ▲ /EN 60598/CLASS I Ⓢ / ▽ / CE / IK07



Suitable for wet locations

A post top luminaire with a large size shade and symmetrical light distribution and a sheppard's crook arm using energy saving compact fluorescent lamps as well as metal halide and high pressure sodium lamps. Developed to compliment the Atlantic Sheppard's crook wall light, Atlantic bollard and Atlantic pillar light. Designed for residential streets and footpath illumination.

Low copper content die-cast aluminium housing with high corrosion resistance and extruded aluminum arm bracket. Stainless steel screws. Durable silicone rubber gasket and clear high impact resistant UV stabilized polycarbonate lens. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear and anodized high purity 95% reflective aluminum reflector.





Product Family









UAA-20671-1-1



Large atlantic dia. 27.5" sheppards crook streetlighting for urban areas.

Model No.	Lamp	Holder	Lumen	Weight	Picture
UAA-20671-1-1	CFQ 26w./CFTR 2X32/42w.	Gx24q-3/4	2X1550/2040/2720	201.0 lb.	1
UAA-20672-1-1	PMH-ED17 2X70w.	MED	2X4000	203.2 lb.	1
UAA-20673-1-1	PMH-ED17 2X100w.	MED	2X6500	203.7 lb.	1
UAA-20674-1-1	PMH-ED17 2X150w.	MED	2X10000	203.7 lb.	1
UAA-20675-1-1	HPS-ED17 2X70w.	MED	2X5450	203.2 lb.	1
UAA-20676-1-1	HPS-ED17 2X100w.	MED	2X8550	203.7 lb.	1
UAA-20677-1-1	HPS-ED17 2X150w.	MED	2X14400	203.7 lb.	1
UAA-20671-1-2	CFQ 26w./CFTR 2X32/42w.	Gx24q-3/4	2X1550/2040/2720	201.0 lb.	2
UAA-20672-1-2	PMH-ED17 2X70w.	MED	2X4000	203.2 lb.	2
UAA-20673-1-2	PMH-ED17 2X100w.	MED	2X6500	203.7 lb.	2
UAA-20674-1-2	PMH-ED17 2X150w.	MED	2X10000	203.7 lb.	2
UAA-20675-1-2	HPS-ED17 2X70w.	MED	2X5450	203.2 lb.	2
UAA-20676-1-2	HPS-ED17 2X100w.	MED	2X8550	203.7 lb.	2
UAA-20677-1-2	HPS-ED17 2X150w.	MED	2X14400	203.7 lb.	2
UAA-20671-2-1	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	201.0 lb.	3
UAA-20672-2-1	PMH-ED17 2x70w.	MED	2X4000	203.2 lb.	3
UAA-20673-2-1	PMH-ED17 2x100w.	MED	2X6500	203.7 lb.	3
UAA-20674-2-1	PMH-ED17 2x150w.	MED	2X10000	203.7 lb.	3
UAA-20675-2-1	HPS-ED17 2x70w.	MED	2X5450	203.2 lb.	3
UAA-20676-2-1	HPS-ED17 2x100w.	MED	2X8550	203.7 lb.	3
UAA-20677-2-1	HPS-ED17 2x150w.	MED	2X14400	203.7 lb.	3
UAA-20671-2-2	CFQ 2x26w./CFTR 2x32/42w.	Gx24q-3/4	2X1550/2040/2720	201.0 lb.	4
UAA-20672-2-2	PMH-ED17 2x70w.	MED	2X4000	203.2 lb.	4
UAA-20673-2-2	PMH-ED17 2x100w.	MED	2X6500	203.7 lb.	4
UAA-20674-2-2	PMH-ED17 2x150w.	MED	2X10000	203.7 lb.	4
UAA-20675-2-2	HPS-ED17 2x70w.	MED	2X5450	203.2 lb.	4
UAA-20676-2-2	HPS-ED17 2x100w.	MED	2X8550	203.7 lb.	4
UAA-20677-2-2	HPS-ED17 2x150w.	MED	2X14400	203.7 lb.	4




Single: EPA=2.40 ft²

Picture 1



(1) Swept shade




Single: EPA=2.36 ft²

Picture 2



(2) Straight shade




Single: EPA=2.53 ft²

Picture 3



(1) Dome top



Single: EPA=2.49 ft²

Picture 4



(2) Cone top