





# Large atlantic dia 27.56" sheppards crook wall streetlighting


IP65   /EN 60598/CLASS I  //CE/IK07



## Suitable for wet locations

A wall mounted outdoor street and amenity lantern with a high performance optical system ensures improved visibility and reduced glare. Designed for pedestrian and residential areas, residential streets, large spaces such as car parks and city center spaces.

Die-cast aluminum housing with high corrosion resistance. Extruded aluminum arm bracket. Stainless steel screws. Durable silicone rubber gasket and clear impact resistant UV stabilized polycarbonate bowl for extra impact resistance. Anodized high purity aluminum side throw reflector. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.




## Product Family







UAA-30631-1-1




Large atlantic dia. 27.56" sheppards crook wall light.


Model No.	Lamp	Holder	Lumen	Weight	Picture
UAA-30631-1-1	CFTR 26/32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	1
UAA-30632-1-1	PMH-ED17 70w.	MED	4000	17.4 lb.	1
UAA-30633-1-1	PMH-ED17 100w.	MED	6500	17.6 lb.	1
UAA-30634-1-1	PMH-ED17 150w.	MED	10000	17.6 lb.	1
UAA-30635-1-1	HPS-ED17 70w.	MED	5450	17.4 lb.	1
UAA-30636-1-1	HPS-ED17 100w.	MED	8550	17.6 lb.	1
UAA-30637-1-1	HPS-ED17 150w.	MED	14400	17.6 lb.	1
UAA-30631-1-2	CFTR 26/32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	2
UAA-30632-1-2	PMH-ED17 70w.	MED	4000	17.4 lb.	2
UAA-30633-1-2	PMH-ED17 100w.	MED	6500	17.6 lb.	2
UAA-30634-1-2	PMH-ED17 150w.	MED	10000	17.6 lb.	2
UAA-30635-1-2	HPS-ED17 70w.	MED	5450	17.4 lb.	2
UAA-30636-1-2	HPS-ED17 70w.	MED	8550	13.8 lb.	2
UAA-30637-1-2	HPS-ED17 150w.	MED	14400	17.6 lb.	2
UAA-30631-2-1	CFTR 26/32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	3
UAA-30632-2-1	PMH-ED17 70w.	MED	4000	17.4 lb.	3
UAA-30633-2-1	PMH-ED17 100w.	MED	6500	17.6 lb.	3
UAA-30634-2-1	PMH-ED17 150w.	MED	10000	17.6 lb.	3
UAA-30635-2-1	HPS-ED17 70w.	MED	5450	17.4 lb.	3
UAA-30636-2-1	HPS-ED17 100w.	MED	8550	17.6 lb.	3
UAA-30637-2-1	HPS-ED17 150w.	MED	14400	17.6 lb.	3
UAA-30631-2-2	CFTR 26/32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	4
UAA-30632-2-2	PMH-ED17 70w.	MED	4000	17.4 lb.	4
UAA-30633-2-2	PMH-ED17 100w.	MED	6500	17.6 lb.	4
UAA-30634-2-2	PMH-ED17 150w.	MED	10000	17.6 lb.	4
UAA-30635-2-2	HPS-ED17 70w.	MED	5450	17.4 lb.	4
UAA-30636-2-2	HPS-ED17 100w.	MED	8550	17.6 lb.	4
UAA-30637-2-2	HPS-ED17 150w.	MED	14400	17.6 lb.	4




Picture 1




Picture 2





Mounting detail



Picture 3



Picture 4



(1) Swept shade



(2) Straight shade



(1) Dome top



(2) Cone top



# Large atlantic dia. 27.56" sheppards crook wall streetlighting LED

IP65 /EN 60598/CLASS I //CE /IK07




## Suitable for wet locations

A wall mounted outdoor street and amenity lantern with a high performance optical system ensures improved visibility and reduced glare. Designed for pedestrian and residential areas, residential streets, large spaces such as car parks and city center spaces.

The luminaires have features such as low glare, long life, limited maintenance and constant lifetime performance. The luminaires use a high quality LED source with low energy consumption.

The Luminaire is rated as class I with the high power LED integral driver. Extruded aluminum arm bracket, low copper content die-cast aluminum housing and clear impact resistant UV stabilized polycarbonate bowl. Stainless steel screws. Durable silicone rubber gasket. The Luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance.




## Product Family









UAA-30639-1-1




## Large atlantic dia 27.56" sheppards crook wall light LED


Model No.	Lamp	Light output	LED colour	Power W	Weight	Picture	Dimmable 1-10V
UAA-30639-1-1-W27	36 LED	2684 lm	2700K	55	29.7 lb.	1	•
UAA-30639-1-1-W30	36 LED	2697 lm	3000K	55	29.7 lb.	1	•
UAA-30639-1-1-W40	36 LED	3083 lm	4000K	55	29.7 lb.	1	•
UAA-30639-1-2-W27	36 LED	2684 lm	2700K	55	29.7 lb.	2	•
UAA-30639-1-2-W30	36 LED	2697 lm	3000K	55	29.7 lb.	2	•
UAA-30639-1-2-W40	36 LED	3083 lm	4000K	55	29.7 lb.	2	•
UAA-30639-2-1-W27	36 LED	2684 lm	2700K	55	29.7 lb.	3	•
UAA-30639-2-1-W30	36 LED	2697 lm	3000K	55	29.7 lb.	3	•
UAA-30639-2-1-W40	36 LED	3083 lm	4000K	55	29.7 lb.	3	•
UAA-30639-2-2-W27	36 LED	2684 lm	2700K	55	29.7 lb.	4	•
UAA-30639-2-2-W30	36 LED	2697 lm	3000K	55	29.7 lb.	4	•
UAA-30639-2-2-W40	36 LED	3083 lm	4000K	55	29.7 lb.	4	•




Mounting detail




Picture 1



Picture 2



Picture 3



Picture 4



(1) Swept shade



(2) Straight shade



(1) Dome top



(2) Cone top