



# Atlantic sheppards crook medium shade wall light

IP55 ✱ ⚡ ⚡ /EN 60598/CLASS I ⚡ /▽/CE/IK07



## Suitable for wet locations

A wall mounted medium shade decorative lantern with a symmetrical light distribution and a sheppard's crook arm bracket. Developed to compliment the Atlantic sheppard's crook post top luminaire. Designed for various applications including car parks, precincts, pathways and town centers. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Low copper content die-cast aluminium housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear.



- 01. Black RAL 9011	- 02. Dark Grey RAL 7043	- 03. White RAL 9003	- 04. Metallic Silver RAL 9006	- 05. Matt Silver RAL 9006	- 06. Bronze RAL 6014

## Product Family



P.324 Atlantic  
P.333 Atlantic small shade  
P.334 Atlantic medium shade  
P.339 Large Atlantic sheppards crook



P.341 Large Atlantic sheppards crook LED  
P.343 Atlantic sheppards crook  
P.499 Atlantic bollard  
P.499 Atlantic 1 pillar light



P.500 Atlantic 2 pillar light  
P.581 Atlantic small shade  
P.582 Atlantic medium shade  
P.589 Atlantic sheppard crook



P.593 Large Atlantic sheppards crook  
P.597 Large Atlantic sheppards crook LED  
P.599 Large Atlantic sheppards crook for urban areas  
P.681 Atlantic small shade







P.681 Atlantic medium shade



Al Towar Park, Dubai - U.A.E



UAA-30181-1-1



Mounting detail



(1) Swept shade




(2) Straight shade




(1) Dome top




(2) Cone top




Picture 1



Picture 2



Picture 3



Picture 4

## Atlantic sheppards crook medium shade wall light.

Model No.	Lamp	Holder	Lumen	Weight	Picture
UAA-30181-1-1	CFQ 18w.	G24q-2	1075	15.2 lb.	1
UAA-30182-1-1	CFQ 26w./CFTR 32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	1
UAA-30183-1-1	PMH-ED17 50w.	MED	2100	17.6 lb.	1
UAA-30184-1-1	PMH-ED17 70w.	MED	4000	17.6 lb.	1
UAA-30185-1-1	PMH-ED17 100w.	MED	6500	19.1 lb.	1
UAA-30186-1-1	PMH-ED17 150w.	MED	10000	19.1 lb.	1
UAA-30187-1-1	HPS-ED17 50w.	MED	3600	17.6 lb.	1
UAA-30188-1-1	HPS-ED17 70w.	MED	5450	17.6 lb.	1
UAA-30189-1-1	HPS-ED17 100w.	MED	8550	19.1 lb.	1
UAA-30190-1-1	HPS-ED17 150w.	MED	14400	19.1 lb.	1
UAA-30181-1-2	CFQ 18w.	G24q-2	1075	15.2 lb.	2
UAA-30182-1-2	CFQ 26w./CFTR 32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	2
UAA-30183-1-2	PMH-ED17 50w.	MED	2100	17.6 lb.	2
UAA-30184-1-2	PMH-ED17 70w.	MED	4000	17.6 lb.	2
UAA-30185-1-2	PMH-ED17 100w.	MED	6500	19.1 lb.	2
UAA-30186-1-2	PMH-ED17 150w.	MED	10000	19.1 lb.	2
UAA-30187-1-2	HPS-ED17 50w.	MED	3600	17.6 lb.	2
UAA-30188-1-2	HPS-ED17 70w.	MED	5450	17.6 lb.	2
UAA-30189-1-2	HPS-ED17 100w.	MED	8550	19.1 lb.	2
UAA-30190-1-2	HPS-ED17 150w.	MED	14400	19.1 lb.	2
UAA-30181-2-1	CFQ 18w.	G24q-2	1075	15.2 lb.	3
UAA-30182-2-1	CFQ 26w./CFTR 32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	3
UAA-30183-2-1	PMH-ED17 50w.	MED	2100	17.6 lb.	3
UAA-30184-2-1	PMH-ED17 70w.	MED	4000	17.6 lb.	3
UAA-30185-2-1	PMH-ED17 100w.	MED	6500	19.1 lb.	3
UAA-30186-2-1	PMH-ED17 150w.	MED	10000	19.1 lb.	3
UAA-30187-2-1	HPS-ED17 50w.	MED	3600	17.6 lb.	3
UAA-30188-2-1	HPS-ED17 70w.	MED	5450	17.6 lb.	3
UAA-30189-2-1	HPS-ED17 100w.	MED	8550	19.1 lb.	3
UAA-30190-2-1	HPS-ED17 150w.	MED	14400	19.1 lb.	3
UAA-30181-2-2	CFQ 18w.	G24q-2	1075	15.2 lb.	4
UAA-30182-2-2	CFQ 26w./CFTR 32/42w.	GX24q-3/4	1550/2040/2720	15.4 lb.	4
UAA-30183-2-2	PMH-ED17 50w.	MED	2100	17.6 lb.	4
UAA-30184-2-2	PMH-ED17 70w.	MED	4000	17.6 lb.	4
UAA-30185-2-2	PMH-ED17 100w.	MED	6500	19.1 lb.	4
UAA-30186-2-2	PMH-ED17 150w.	MED	10000	19.1 lb.	4
UAA-30187-2-2	HPS-ED17 50w.	MED	3600	17.6 lb.	4
UAA-30188-2-2	HPS-ED17 70w.	MED	5450	17.6 lb.	4
UAA-30189-2-2	HPS-ED17 100w.	MED	8550	19.1 lb.	4
UAA-30190-2-2	HPS-ED17 150w.	MED	14400	19.1 lb.	4

## Atlantic sheppards crook medium shade wall light LED.

\*Contact factory for LED 50w & 90w option available

Model No.	Lamp	Light output	LED colour	Power W	Weight	Picture	Dimmable 1-10V
UAA-32114-1-1-W27	1 LED	1850 lm	2700K	41	18.9 lb.	1	•
UAA-32114-1-1-W30	1 LED	1969 lm	3000K	41	18.9 lb.	1	•
UAA-32114-1-1-W40	1 LED	2372 lm	4000K	41	18.9 lb.	1	•
UAA-32114-1-2-W27	1 LED	1850 lm	2700K	41	18.9 lb.	2	•
UAA-32114-1-2-W30	1 LED	1969 lm	3000K	41	18.9 lb.	2	•
UAA-32114-1-2-W40	1 LED	2372 lm	4000K	41	18.9 lb.	2	•
UAA-32114-2-1-W27	1 LED	1850 lm	2700K	41	18.9 lb.	3	•
UAA-32114-2-1-W30	1 LED	1969 lm	3000K	41	18.9 lb.	3	•
UAA-32114-2-1-W40	1 LED	2372 lm	4000K	41	18.9 lb.	3	•
UAA-32114-2-2-W27	1 LED	1850 lm	2700K	41	18.9 lb.	4	•
UAA-32114-2-2-W30	1 LED	1969 lm	3000K	41	18.9 lb.	4	•
UAA-32114-2-2-W40	1 LED	2372 lm	4000K	41	18.9 lb.	4	•