

MELBOURNE 7 (UMEL-60062)**Product description**

11.4" Diameter | Discreet | Flush
In-Ground Outdoor Light
120-277v Input Voltage
Up to 1157 Lumen Output
RGBW – Unlimited Possibilities of Color
Scenes / Color Transitions through a
DMX Controller (Stick-DE3 Sold
Separately)
Externally adjustable tilt up to 25° along
with 360° rotation
Narrow or Wide Optical Pattern

**Luminaire Structure**

- | | | |
|---|---|--|
| <ul style="list-style-type: none"> - Die-cast stainless steel in grade 316 - Body is pre-treated before powder coating ensuring high corrosion resistance - Front ring in grade 316 stainless steel - Externally adjustable: Tilt 25°, Rotation 360° for UMEL-60051, UMEL-60052, UMEL-60053, UMEL-60061, UMEL-60062, UMEL-60063 - Single cable entry, through wiring upon request - One cable gland supplied with 2.5ft outdoor cable | <ul style="list-style-type: none"> - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear, .59" thick, toughened glass - Recessing box in high-density polyethylene is included - Suitable for drive-over with a maximum load of 11,000LBS | <ul style="list-style-type: none"> - Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 31 mph - Load is transferred by the housing to the foundation - One glass suction cup for easy installation is included in each item list on the order - The distance between the luminaire and the illuminated surface should be at least 1.6ft |
|---|---|--|

Optic

W

Product color

00 - Stainless Steel

