Vancouver 5 Light Column





THE POINTS PROPERTY OF THE PARTY OF THE PART NATE REPORT OF THE PROPERTY OF THE PARTY OF **DOWNLIGHT** 39w COB 1336 Lumens


FLOODLIGHT 21w COB 1673 Lumens

IP65 Suitable for wet locations

IK08

Impact Resistant [Vandal Resistant]

Weight 115.5 lbs



Construction

Aluminum Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength , clean detailed product lines and excellent heat dissipation.

Pre paint

48 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and LMb Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux. output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

<u>Surge Suppression</u> Standard 10kv surge suppressor provided with all fixtures.

BUG Rating B1 - U0 - G0

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

UV Stabilized 4.9Mil thick powder coat paint and baked at 200° C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

Inspired by Nature Finishes
The Inspired by nature Finishing is a unique system of
decorative powder coating. Our metal decoration process can
easily transform the appearance of metal or aluminum product into a wood grain finish.

This patented technology enables the simulation of wood grain, and even marble or granite finish through the use of decorative

The wood grain finish is so realistic that it's almost undistinguishable from real wood, even from a close visual inspection. The system of coating permeates the entire thickness of the coat and as a result, the coating cannot be removed by normal rubbing, chipping, or scratching.

<u>The Coating Process</u>
After pre-treatment the prepared parts are powder coated with a specially formulated polyurethane powder. This powder provides protection against wear, abrasion, impact and corrosion and acts as the relief base color for the finalized metal

The component is then wrapped with a sheet of non-porous film with the selected decoration pattern printed on it using special high temperature inks.

This printed film transfer is vacuum-sealed to the surface for a complete thermo print and then transferred into a customized oven. The oven transforms the ink into different forms within the paint layer before it becomes solid. Finally, the film is removed, and a vivid timber look on aluminum remains

Wood grain coating can create beautiful wood-looking products of any sort. There are over 300 combinations of designs currently in use. Wood grains can be made with different colors, designs, etc.

Our powder coatings are certified for indoor and outdoor applications and are backed by a comprehensive warranty. These coatings rise to the highest conceivable standard of performance excellence and design innovation.

Added Benefits

- Resistance to salt-acid room, accelerated aging Boiling water, lime and condensed water resistant
- Anti-Graffiti, Anti-Slip, Anti-Microbial, Anti-Scratch Super durable (UV resistant)
- · TGIC free (non-toxic)

Hardware

Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Precise optic design provides exceptional light control and precise distribution of light.

<u>Lumen - Maintenance Life</u> L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Total urban realm lighting solution. Optional heights, accent spotlights, accessories and decorative lattice panels.

A stylish Dark Sky Compliant square high performance light column with downward light distribution using LED lamps. This light column offers optimal visual comfort through glare control by utilizing a controlled optics designed by Ligman. These columns have a square design providing a unique wide light distribution, offering an architecturally appealing clover leaf pattern on the paving. The internal sides of the supporting pillars are accented by light from the LED.

Color temperature 2700K, 3000K, 3500K and 4000K. The minimalistic shape provides distinctive lighting effects by night and decorative urban effect during the day. Suitable for pedestrian areas, precincts, building surrounds, shopping centers, squares and parks. The Vancouver Column comes standard with a unique waterproof internal driver housing compartment that is situated at the top of the pole to stop water and dust from entering the electrical components.

This fixture is supplied completely wired with powercord and waterproof gland from the driver enclosure to the base of the column to ensure quick trouble-free installation.

The Vancouver has a specially designed anchor bolt mounting base that is partially buried below ground level to provide a flush fixture finish with the surface, but maintains the rigidity that is required when installing light columns. This ensures that the anchor bolts are not seen and therefore eliminates the necessity for an anchor bolt cover. (review installation instructions before installing the anchor bolts.)

Custom column heights are available, please specify. Provided with anchor bolts (the root mount kit is an option and is an adder)

Reduced custom wattages can be provided to suit customer requirements. (Specify total watt requirement per fixture) Designed to complement the Vancouver bollard UVA-10001. This product is provided complete with anchor bolts and laser cut steel bolt template.

Additional Options (Consult Factory For Pricing)



UVA-20021

Vancouver 5 Light Column




PROJECT DATE QUANTITY NOTE **TYPE** ORDERING EXAMPLE | UVA - 20021 - 39w - M - W30 - 02 - 120/277v - Options UVA-20021 **LAMP** FLOODLIGHT BEAM LED COLOR **FINISH COLOR VOLTAGE** DOWNLIGHT M - Medium 23° W27 - 2700K 01 - BLACK RAL 9011 120/277v 39w COB W - Wide 32° W30 - 3000K Other - Specify 02 - DARK GREY RAL 7043 1336 Lumens VW - Very Wide 47 W35 - 3500K 03 - WHITE RAL 9003 W40 - 4000K 04 - METALLIC SILVER RAL 9006 FLOODLIGHT 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 21w COB 1673 Lumens 07 - CUSTOM RAL INSPIRED BY NATURE FINISHES SW01 - OAK FINISH SW02 - WALNUT FINISH SW03- PINE FINISH DF - DOUGLAS FIR FINISH CW - CHERRY WOOD FINISH THERE IS AN ADDITIONAL COST FOR THESE FINISHES **NW - NATIONAL WALNUT FINISH ADDITIONAL OPTIONS** SU01 - CONCRETE FINISH SU02 - SOFTSCAPE FINISH DIM - 0-10v Dimming A90891 - NEMA 7 SU03 - STONE FINISH NAT - Natatorium Rated A91791 - Square Power Plug **SU04 - CORTEN FINISH** GFCI - GFCI Box A91291 - Speaker A91091 - WiFi **HGT - Custom Height (Specify)** A90991-U - Zhaga Book 18 Mounted On Top of Fixture A91691-L2 - Motion Sensor (Up to 10ft) A90991-D - Zhaga Book 18 Mounted Below Fixture A91691-L7 - Motion Sensor (Up to 40ft) A91191 - Camera A91491 - Electric Vehicle Charger A91391 - Intercom A91991 - EO Hub UP - Uplight MAN TO SECRETARISM SECRETARIA SECRETARISM SECRETARISM SEC ACADE STREET, SESSE SESSES SESSES SESSES DICHROIC COLOR FILTERS A20216 - Red Color Filter A20217 - Blue Color Filter A20218 - Amber Color Filter A20219 - Green Color Filter




Example: Two-Tone Inspired by

Nature Finish

Vancouver Product Family




- UVA-20001-70w-6350lm [9.4"x9.4"-14.7"]
- UVA-20001-60w-6084lm [9.4"x9.4"-14.7']
- UVA-20001-50w-5576Im [9.4"x9.4"-14.7"]
- UVA-20001-40w-2969Im [9.4"x9.4"-14.7']











- UVA-20021-39/21w-1336/1673lm [9.4"x9.4"-13.3']
- UVA-20022-39/2x21w-1336/2x1673lm [9.4"x9.4"-14.5"]
- UVA-20023-39/3x21w-1336/3x1673Im [9.4"x9.4"-15.7']


- Vancouver 6 • UVA-20031-39/21w-1167/1673lm [9.4"x9.4"-13.3']
- UVA-20032-39/2x21w-1167/2x1673lm [9.4"x9.4"-14.5"]




- UVA-20041-39/21w-1670/1673lm [9.4"x9.4"-13.3']
- UVA-20042-39/2x21w-1670/2x1673Im [9.4"x9.4"-14.5"] • UVA-20043-39/3x21w-1670/3x1673lm [9.4"x9.4"-15.7']



• UVA-20051-40w-1336lm [9.4"x9.4"-12.1']



• UVA-20061-40w-1167lm [9.4"x9.4"-12.1']




• UVA-20071-40w-1670lm [9.4"x9.4"-12.1']

- UVA-20033-39/3x21w-1167/3x1673lm [9.4"x9.4"-15.7']



Vancouver 12

• UVA-10031-21w-490lm [9.4"x9.4"-39.3']



• UVA-10041-21w-704lm [9.4"x9.4"-39.3']



• UVA-70001-8w-331lm [6.3"x6.3"-15.7"]




• UVA-70011-21w-815lm [9.4"x9.4"-15.7"]

Vancouver 11 • UVA-10021-21w-570lm [9.4"x9.4"-39.3']



Vancouver 16

- UVA-20111-33w-1429Im [9.4"x9.4"-13.3']
- UVA-20112-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20113-99w-5716lm [9.4"x9.4"-15.7']
- UVA-20114-132w-7145Im [9.4"x9.4"-17']



Vancouver 17

- UVA-20121-33w-2858 Im [9.4"x9.4"-13.3']
- UVA-20122-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20123-99w-5716lm [9.4"x9.4"-15.7']
- UVA-20124-132w-7145lm [9.4"x9.4"-17']



Vancouver 18

- UVA-20131-33w-2858lm [9.4"x9.4"-13.3']
- UVA-201312-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20133-99w-5716Im [9.4"x9.4"-15.7"]
- UVA-20134-132w-7145lm [9.4"x9.4"-17']



Vancouver 19

- UVA-20141-33w-2858lm [9.4"x9.4"-13.3']
- UVA-20142-66w-4287lm [9.4"x9.4"-14.5']
- UVA-20143-99w-5716Im [9.4"x9.4"-15.7'] • UVA-20144-132w-7145Im [9.4"x9.4"-17"]




Vancouver 20

• UVA-20151-33w-1429lm [9.4"x9.4"-12.1']


Vancouver 21

• UVA-20161-33w-1429Im [9.4"x9.4"-12.1']



Vancouver 22

• UVA-20171-33w-1429lm [9.4"x9.4"-12.1']



Vancouver 23

• UVA-20181-33w-1429Im [9.4"x9.4"-12.1']



Vancouver 24

• UVA-30001-8w-331lm [6.3"x6.3"-15.7"]



Vancouver 25

• UVA-30011-21w-570lm [6.3"x6.3"-23.6"]



Vancouver 26

• UVA-30012-21w-490lm [6.3"x6.3"-23.6"]



Vancouver 27

• UVA-30013-21w-740Im [6.3"x6.3"-23.6"]



Vancouver 28

• UVA-30021-39w-1336lm [9.4"x9.4"-39.3"] • UVA-30031-33w RGBW-429Im [9.4"x9.4"-39.3"]




Vancouver 29

• UVA-30022-39w-1167lm [9.4"x9.4"-39.3"] • UVA-30032-33w RGBW-1158lm [9.4"x9.4"-39.3"]



Vancouver 30

• UVA-30023-39w-1670Im [9.4"x9.4"-39.3"] • UVA-30033-33w RGBW-439lm [9.4"x9.4"-39.3"]



Vancouver 42

Vancouver 43


Vancouver 44

Vancouver 45

Vancouver 45

Vancouver 46

• UVA-20201-39/2\iv-2781/5x1688\im [9.4"x 9.4"-14.5"] • UVA-20213-39/3x2\iv-2781/5x88\im [9.4"x 9.4"-15.7]] • UVA-20213-39/3x2\iv-2781/3x1688\im [9.4"x 9.4"-15.7]] • UVA-20213-39/2\iv-2781/3x1688\im [9.4"x 9.4"-15.7]]



Vancouver 60
Vancouver 61
Vancouver 62
Vancouver 63
Vancouver 64

UVA-20281-76w-4140lm [9.4'x9.4'-12']
UVA-20282-76w-4140lm [9.4'x9.4'-12']
UVA-70021-13w-437lm [6.3'x6.3'-15.7']
UVA-70021-13w-437lm [6.3'x6.3'-15.7']



• UVA-70041-8w-165lm [6.3"x6.3"-15.7"]



Vancouver 66

• UVA-70051-21w-410lm [9.4"x9.4"-15.7"]



Vancouver 67

• UVA-30041-20w-1326Im [6.3."x6.3"-23.6"]



Vancouver 68

• UVA-30042-20w-1326lm [6.3."x6.3"-23.6"]



Vancouver 69

• UVA-30043-20w-1326lm [6.3."x6.3"-23.6"]



Vancouver 70

• UVA-30051-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 71

• UVA-30052-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 72

• UVA-30053-40w-2781lm [9.4"x9.4"-39.3"]