


LUMINAIRE SPECIFICATION


Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100


Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65: Suitable for Wet Locations IK09: Impact Resistant (Vandal Resistant)










Mounting detail



Tenon arm bracket

USY-30918

Syndy symmetrical indirect wall light LED square top

A decorative wall lantern with excellent downward symmetrical light distribution and visual appeal. The precision optical system gives very low glare rating, while reducing light pollution. Developed to compliment Syndy indirect post top and street lanterns. Designed for lighting of entrances, footpaths and car parks.

Low copper content die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. White painted aluminum reflector on the top of luminaire.

Physical Data

Length: 41.14" Height: 29.98" Weight: 29.7 lbs

Lamp

□ 41w - 1875lm - White - LED @

LED Color (Please Specify)

- □ W27 2700K
- □ W30 3000K
- □ W40 4000K

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other


Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014
- □ 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006
- □ 07- Custom RAL _









PROJECT:

QUANTITY:

NOTE:

DATE:



