



For Installation of Veranda 6 pillar light LED. Model. UVR-70311,UVR-70312 and UVR-70313

Product drawing (dimensions)

NOTE: THIS PRODUCT HAS BEEN PROVIDED WITH A SO CORD FOR CONNECTION TO INCOMING POWER. A WATERPROOF SPLICE SHOULD BE USED IF THIS METHOD OF CONNECTION IS TO BE USED. IF THE CONTRACTOR CHOOSES NOT TO USE THIS METHOD, THE GEARBOX COVER SHOULD BE REMOVED AND POWER CORD RUN THROUGH THE WATERPROOF GLAND AND CONNECTED TO THE DRIVER. PLEASE ENSURE THAT THE WATERPROOF GLAND IS PROPERLY TIGHTENED TO ENSURE NO MOISTURE INGRESS.

A WATERPROOF JUNCTION BOX CAN ALSO BE INSTALLED BY OTHERS BELOW THE FIXTURE FOR POWER CONNECTION USING THE FACTORY PROVIDED SO CORD

THE INSTALLATION METHOD MUST COMPLY TO LOCAL CODE REQUIREMENTS



Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NE Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100
www.ligmanlightingusa.com